Что у ней внутри:

Зачем и как
интерпретировать ML-модели

**Дмитрий Колодезев, ООО Промсофт
«Семинар Невозможного», 2021.09.23**

План

- Машинное обучение — оно везде
- Что это, кстати, такое
- Как делить выигрыш в карты
- Чем больше отчетов, тем хуже
- Как понять нейронную сеть
- Где интересно
- Как быть

История вопроса

— Вот, извольте видеть, так называемая эвристическая машина, — сказал старичок.

— Точный электронно-механический прибор для отвечания на любые вопросы, а именно на научные и хозяйственные.

А.Б. Стругацкие, «Сказка о Тройке»

Осторожно, роботы!

ОСТОРОЖНО, ЛЮДИ

DARPA, eXplainable AI

- We are entering a new age of AI applications
- Machine learning is the core technology
- Machine learning models are opaque, non-intuitive, and difficult for people to understand

DoD and non-DoD Applications

Transportation

Security

Medicine

Finance

Legal

Military

- Why did you do that?
- Why not something else?
- When do you succeed?
- When do you fail?
- When can I trust you?
- How do I correct an error?

Кстати, что такое ML?

Machine learning is the science of getting computers to act without being explicitly programmed *

Software 2.0 is code written by the optimization based on an evaluation criterion (such as “classify this training data correctly”) *

Машинное обучение -
автоматизированное построение удобной
нам проекции признакового пространства

Линейно разделяй и в.

- Это удобное пространство
- Линейно разделимое
- Чутко повернуть, сдвинуть, сплющить
- И вообще будет огонь

Kernel Trick

- Сколько ни крути
- А давайте перейдем в полярные координаты?

А что если

<http://colah.github.io/posts/2014-03-NN-Manifolds-Topology/>

Тяни сильнее

- Руби через узел
- Нейронки так и делают
- Почти разделимо
- Кому-то не повезло
- Для практики достаточно

Тянем бублики наощупь

Как-попало-проекция

Weighted Sums of Random Kitchen Sinks: Replacing minimization with randomization in learning

Ali Rahimi
Intel Research Berkeley
Berkeley, CA

Benjamin Recht
Caltech IST
Pasadena, CA

Abstract

Randomized neural networks are immortalized in this well-known AI Koan:

In the days when Sussman was a novice, Minsky once came to him as he sat hacking at the PDP-6.

"What are you doing?" asked Minsky. "I am training a randomly wired neural net to play tic-tac-toe," Sussman replied. "Why is the net wired randomly?" asked Minsky. Sussman replied, "I do not want it to have any preconceptions of how to play."

Minsky then shut his eyes. "Why do you close your eyes?" Sussman asked his teacher. "So that the room will be empty," replied Minsky. At that moment, Sussman was enlightened.

We analyze shallow random networks with the help of concentration of measure inequalities. Specifically, we consider architectures that compute a weighted sum of their inputs after passing them through a bank of arbitrary randomized nonlinearities. We identify conditions under which these networks exhibit good classification performance, and bound their test error in terms of the size of the dataset and the number of random nonlinearities.

<https://www.youtube.com/watch?v=x7psGHgatGM>

<https://people.eecs.berkeley.edu/~brecht/papers/08.rah.rec.nips.pdf>

Да не угаснет пламя

Artyom Palvelev 13 days ago

Тут произошёл наброс от , что в общем-то всё то же, что могут делать трансформеры, можно делать и без них просто на MLP: <https://arxiv.org/abs/2105.08050> Получилось на sentiment classification примерно на уровне BERT, а на ImageNet (на последовательностях из кусочков картинок) что-то на уровне DeiT.

Pay Attention to MLPs

Transformers have become one of the most important architectural innovations in deep learning and have enabled many breakthroughs over the past few years. Here we propose a simple network...

[11 more replies](#)

bonlime 12 days ago

следующий наброс после этого, что даже MLP не нужен и любое смешивание фичей в spatial пространстве работает. [FNet: Mixing Tokens with Fourier Transforms](#) авторы тут используют Fourier, но у них есть и эксперименты со случайной матрицей, которая тоже работает

<https://arxiv.org/abs/2105.08050> <https://arxiv.org/abs/2105.03824>

Как в жизни?

- Гипотеза о многообразии
- <https://deeprai.org/machine-learning-glossary-and-terms/manifold-hypothesis>
- http://www.mit.edu/~mitter/publications/121_Testing_Manifold.pdf

Гипотеза о многообразии

ИТОГО

ML-алгоритмы строят проекции:

- Бесконтрольно
- Удобные им
- Нелогичные
- Нелинейные
- Немыслимые
- Технически при этом никакой магии нет

В принципе все понятно

<https://www.arxiv-vanity.com/papers/1606.00373/>

OpenAI Microscope

Models

ResNet v2 50

block4/unit_3/conv2/Relu

AlexNet

1,001 predictions/Softmax

AlexNet (Places)

1,001 logits/Conv2D

Inception v1

2,048 block4/unit_3/add

Inception v1 (Places)

3,3 block4/unit_3/conv2...

VGG 19

1,1

Inception v3

2,048 block4/unit_2/add

Inception v4

3,3

1,1

2,048 block4/unit_1/add

3,3

1,1

ResNet v2 50

1,024 block3/unit_6/add

CLIP Resnet 50 v0

3,3

1,1

CLIP Resnet 50

1,024 block3/unit_5/add

CLIP Resnet 101

3,3

1,1

CLIP Resnet 50 4x

1,024 block3/unit_4/add

CLIP Resnet 50 16x

3,3

1,1

1,024 block3/unit_3/add

3,3

1,1

1,024 block3/unit_2/add

3,3

1,1

1,024 block3/unit_1/add

Type: Relu

Channels: 512

Convolution: [3,3]

Technique

- Feature Visualization
- DeepDream
- Dataset Samples
- Caricature
- Text Feature Visualization

An artificial, optimized image that maximizes activations of the given unit. [Read more](#)

Params

Optimization Objective

- channel
- neuron

View

Image Size

Resize Behavior

- Crop image
- Scale image

Проблема не в моделях

<https://openai.com/blog/microscope/>

buriy ✨ 1 year ago

это надо тыкать в лицо показывать тем людям, что утверждают, что нейросети -- чёрный ящик, не интерпретируемы, итп.

buriy ✨ 1 year ago

(нейросети конечно плохо интерпретируемы, но по совсем другим причинам -- у нас мозг слишком маленький, чтобы принять даже часть интерпретации чужой нейросети, так что нужно применять специальные алгоритмы, чтобы снизить размер до размера мозга обывателя: термины подобрать наиболее знакомые, факторы оставить только самые ключевые...) (edited)

d_key 1 year ago

Строго говоря, эти картинки не делают предикт данных сетей более интерпретируемым. Он скорее помогает понять как они работают в целом, но на вопрос - что нужно променять в этой конкретной собаке, чтобы она была кошкой? почему это собака, а не кошка? чем эта собака так отличается от других собак, что ее считают за кошку - картинки не отвечают. А интерпретируемость про это тоже

d_key 1 year ago

тот же самый shar или lime или Grad-Cam даст ответ на эти вопросы

Но проблема есть

- Разработчик. Подсказки:
 - Почему она здесь ошиблась?
 - Какие примеры научили ее плохому?
- Пользователь. Предсказуемость:
 - Чего от нее ждать?
 - Границы применимости?
- Следователь. Соответствие требованиям:
 - Почему она сделала это?
 - Кто за это ответит?

ВОЗМОЖНО ЛИ ЭТО?

- «У мене внутре... гм... не... неонка»
- Внутре смотрите,
где у нее анализатор и думатель..
А.Б. Стругацкие, «Сказка о Тройке»

Подходы

- Визуализация
- Упрощение
- Локальные объяснения
- Важность признаков
- Объяснение на примерах
- Текстовые объяснения

а еще

- Влияние обучающих примеров
- Граф взаимодействия

Варианты

- Суррогатные модели
 - [Shap](#), [Grad-CAM](#)
- Ближайшие соседи
- Прототипы и критики
 - [MMD-critic](#), обычно вручную
- Якоря
 - [Alibi](#)
- Тысячи их

Shapley Values

<https://clearcode.cc/blog/game-theory-attribution/>

Shapley Values

<https://clearcode.cc/blog/game-theory-attribution/>

Shapley Values

- Оценим, насколько выигрыш обусловлен участием того или иного игрока
- $(4+0+4+4+4+3) / 6 \sim 3,16$ доля игрока А
- $(7+7+10+3+9+10) / 6 \sim 7,66$ доля игрока В
- $(8+12+5+12+6+6) / 6 \sim 8,16$ доля игрока С

Признаки как игроки

Водопад

<https://github.com/slundberg/shap>

Force plot

SHAP и структура данных

SHAP — глобальный

<https://github.com/slundberg/shap>

УЧИТЕ

<https://arxiv.org/pdf/2002.11097.pdf>

Problems with Shapley-value-based explanations as feature importance measures

<https://papers.nips.cc/paper/2020/file/0d770c496aa3da6d2c3f2bd19e7b9d6b-Paper.pdf>

Asymmetric Shapley values

<https://papers.nips.cc/paper/2020/file/32e54441e6382a7fbacbbaf3c450059-Paper.pdf>

Causal Shapley Values

SHAP — ВЛИЯЮЩИЕ ТОЧКИ

Saliency map

- Подсветим точки градиентом
- Можно наложить маску на исходное изображение
- На что обратила внимание != Чем руководствовалась

Saliency map

Figure 2: Example of a saliency map explanation of a True Positive (TP) image for the label “train”. It highlights the contours of the lines below the train. A possible interpretation is that the CNN has learned to recognise trains when rails are present.

by the CNN. Our results indicate that when saliency maps were available, participants answered correctly more frequently than when they were absent (60.7% vs. 55.1%, $p = 0.045$). However, the overall performance was generally low even with the presence of saliency maps.

Our data indicates that saliency maps influenced people to notice saliency-maps-features. However, it is unclear if such explanation draw them away from considering other attributes that are usually not highlighted by saliency maps.

Figure 3: Example of a saliency map explanation of a False Positive (FP) image for the label “train”. A possible interpretation is that edges in the lower part appeared similar to rails, which could explain this error.

Grad-CAM

<http://gradcam.cloudcv.org/>

Grad-CAM

Resnet50:

Category	Image	GradCAM	AblationCAM	ScoreCAM
Dog
Cat

<https://github.com/jacobgil/pytorch-grad-cam>

Лишь бы график красивый

- У нас был датасет
- Пачка графиков
- 11 датасатанистов
- SHAP
- GAM
- ...

CHI 2020 Paper

CHI 2020, April 25–30, 2020, Honolulu, HI, USA

Interpreting Interpretability: Understanding Data Scientists' Use of Interpretability Tools for Machine Learning

Harmanpreet Kaur¹, Harsha Nori², Samuel Jenkins²,
Rich Caruana², Hanna Wallach², Jennifer Wortman Vaughan²

¹University of Michigan, ²Microsoft Research
harmank@umich.edu, {hanori,sajenkin,rcaruana,wallach,jenn}@microsoft.com

ABSTRACT

Machine learning (ML) models are now routinely deployed in domains ranging from criminal justice to healthcare. With this newfound ubiquity, ML has moved beyond academia and grown into an engineering discipline. To that end, interpretability tools have been designed to help data scientists and machine learning practitioners better understand how ML models work. However, there has been little evaluation of the extent to which these tools achieve this goal. We study data scientists' use of two existing interpretability tools, the InterpretML implementation of GAMs and the SHAP Python package. We conduct a contextual inquiry (N=11) and a survey (N=197) of data scientists to observe how they use interpretability tools to uncover common issues that arise when building and evaluating ML models. Our results indicate that data scientists over-trust and misuse interpretability tools. Furthermore, few of our participants were able to accurately describe the visualizations output by these tools. We highlight qualitative themes

These developments create countless opportunities for impact, but with these opportunities come new challenges. ML models have been found to amplify societal biases in datasets and lead to unfair outcomes [4, 9, 29]. When ML models have the potential to affect people's lives, it is critical that their developers are able to understand and justify their behavior. More generally, data scientists and machine learning practitioners cannot debug their models if they do not understand their behavior. Yet the behavior of complex ML models like deep neural networks and random forests is notoriously difficult to understand.

Faced with these challenges, the ML community has turned its attention to the design of techniques aimed at *interpretability*¹ [14, 39]. These techniques generally take one of two approaches. First, there are ML models that are designed to be inherently interpretable, often due to their simplicity, such as point systems [25, 68] or generalized additive models (GAMs) [10]. Second, there are techniques that provide post-

<http://www.jennwv.com/papers/interp-ds.pdf>

Прозрачное хуже

Manipulating and Measuring Model Interpretability

With machine learning models being increasingly used to aid decision making even in high-stakes domains, there has been a growing interest in developing interpretable models. Although many supposedly interpretable models have been proposed, there have been relatively few experimental studies investigating whether these models achieve their intended effects, such as making people more closely follow a model's predictions when it is beneficial for them to do so or enabling them to detect when a model has made a mistake. We present a sequence of pre-registered experiments ($N = 3,800$) in which we showed participants functionally identical models that varied only in two factors commonly thought to make machine learning models more or less interpretable: the number of features and the transparency of the model (i.e., whether the model internals are clear or black box). Predictably, participants who saw a clear model with few features could better simulate the model's predictions. However, we did not find that participants more closely followed its predictions. Furthermore, showing participants a clear model meant that they were *less* able to detect and correct for the model's sizable mistakes, seemingly due to information overload. These counterintuitive findings emphasize the importance of testing over intuition when developing interpretable models.

Еще не все

- Интерпретация эмбеддингов
 - Projector
 - Граф близости эталонов
- Графовые модели
- Трансформеры и внимание
- Топологические ML-модели
- Causal Inference
- Reinforcement Learning

Что делать

- Не пропускать этап EDA
- Разрабатывать инструменты
 - Есть пара идей для дипломной работы
- Учиться интерпретировать модели
 - Курс от ODS.AI, стартует в октябре
- Думать, что делаешь

Вопросы

Слайды тут

dkolodezev

promsoft

dkolodezev

d_key

dmitry_kolodezev

<https://kolodezev.ru/download/interpretable20210923.pdf>